Mitutoyo



## PH-A14 Profile Projector and 2D Processor Packages


-0.4504

-

Horizontal projector equipped with highly accurate linear glass scales and touch screen M2 geometric measurement display



**NEU** Products



**Graphics-based "Part View" constructions** Generate popular construction types, like Distances and Tangent Lines, from within the graphical part view.

### Features:

- ø14" Screen, Horizontal Projector
- 8" x 4" Travel T Slot table for accessories
- Linear Glass Scales for accurate movement
- Profile and Fiber Optic Surface Illumination
- Easy to use all-in-one PC Touch Screen Display
- M2 Geometric 2D Measurement Software
- Optional Edge Detection (64PKA155) for fast and repeatable measurements

FULL PACKAGES			
Order No.	Description List		
64PKA154	PH-A14 PROFILE PROJECTOR - WITH TOUCH SCREEN M2 GEOMETRIC DISPLAY <b>\$10,490.0</b>		
64PKA155	PH-A14 PROFILE PROJECTOR - WITH OPTICAL EDGE DETECTION AND TOUCH SCREEN M2 <b>\$11,900.00</b> GEOMETRIC DISPLAY		
RETROFIT PACKAGES			
64PKA156	M2 2D Data Processing Unit with software and hardware including a tablet PC. Also includes installation and calibration on the customer's existing PH-A14		
64PKA157	M2 2D Data Processing Unit with Edge Detection software and hardware including a tablet PC. Also includes installation and calibration on the customer's existing PH-A14	\$5,500.00	
4 1 1	installation and ADLA associated s	PL (C. )	

(Includes installation and A2LA accredited calibration)

### 

**Geometric tolerancing** Measure features, set nominals, apply tolerances and view deviation results with only a few quick clicks.



**Reports** Flexibility for report contents and formatting allows for full customization of the data format, header information, and header and footer graphics.

### **PH-A14 Specifications**

Model No.		PH-A14	
Base Unit		172-810-10A*	
Projected Image		Inverted image	
Protractor screen	Effective diameter	14" /356mm	
	Screen material	Fine ground glass	
	Reference line	Cross hair line	
	Screen rotation	±360°, fine feed and clamp	
	Angle display	Vernier reading, Resolution: 2'	
Projection lens		Standard accessory: 10x(172-011), Optional accessories: 20X, 50X, 100X	
Magnification accuracy	Contour illumination	±0.1% or less	
	Surface illumination	±0.15% or less	
Contour illumination	light source	Halogen bulb(24V 150W)	
	Optical system	Telecentric system	
	Functions	Heat-absorbing filter, Cooling fan	
Surface illumination	light source	Halogen bulb(24V 150W)	
	Optical system	Twin fiber optic illumination	
XY Stage	Table travel (X-axis)	8" / 203.2mm	
	Table size(X, Z)	16 x 6" / 407 x 153mm	
	Vertical travel (Y-axis)	4" / 101.6mm	
	Resolution	.00005" / 0.001mm*	
	Measuring Unit	Built in Linear scale	
	Max. workpiece width	See (L) on page I-12	
	Max. workpiece load	100lbs / 45kg	
Power supply		120V AC, 50/60Hz	
Mass		308lbs / 140kg	
Standard accessories		10x projection lens set, work stage, power cord, halogen bulb,fuse, grounding wire, allen wrench	

\*Counter not included

# Mitutoyo

Mitutoyo America Corporation www.mitutoyo.com

1-888-MITUTOYO (1-888-648-8869)

### **M<sup>3</sup>** Solution Centers:

Aurora, Illinois (Headquarters) Boston, Massachusetts Charlotte, North Carolina Cincinnati, Ohio Detroit, Michigan Los Angeles, California Birmingham, Alabama Seattle, Washington Houston, Texas



### Find additional product literature and our product catalog

www.mitutoyo.com

Note: All information regarding our products, and in particular the illustrations, drawings, dimensional and performance data contained in this printed matter as well as other technical data are to be regarded as approximate average values. We therefore reserve the right to make changes to the corresponding designs. The stated standards, similar technical regulations, descriptions and illustrations of the products were valid at the time of printing. In addition, the latest applicable version of our General Trading Conditions will apply. Only quotations submitted by ourselves may be regarded as definitive. Specifications are subject to change without notice.

Mitutoyo products are subject to US Export Administration Regulations (EAR). Re-export or relocation of our products may require prior approval by an appropriate governing authority.

#### Trademarks and Registrations

Designations used by companies to distinguish their products are often claimed as trademarks. In all instances where Mitutoyo America Corporation is aware of a claim, the product names appear in initial capital or all capital letters. The appropriate companies should be contacted for more complete trademark and registration information.



Sensor Systems

Test Equipment and Seismometer

Digital Scale and DRO Systems

Small Tool Instruments and Data Management

© 2018 Mitutoyo America Corporation 0418-00 • FOR WEB ONLY • June 2018