

Mitutoyo

Mitutoyo Quality

CNC Coordinate Measuring Machine CRYSTA-Apex V Series

Coordinate Measuring Machines



Bulletin No. 2297(2)

To the next level

CRYSTA - Apex *V* SERIES

500/700/900/1200/1600/2000 Series

Introducing a new generation CNC coordinate measuring machine focused on accuracy, speed, and versatility.

We are proud to unveil our CRYSTA-Apex V Series that delivers faster measurement of small- to large sized parts without compromising the measuring machine's inherent accuracy, and helps make the smart factory a reality.



A brand new CMM design that provides cutting-edge capability in an extensive series of models that covers practically any measurement application in the small - to large size parts range.

The aesthetic design features bold colors that enhances a precision measuring instrument of the IoT age. Offering a choice of models for measuring from small to large sized workpieces, the CRYSTA-Apex V Series delivers advances in accuracy, speed and versatility in this class of CMM.



CRYSTA-Apex V544

Measuring range


X: 500 mm
Y: 400 mm
Z: 400 mm



CRYSTA-Apex V776

Measuring range

X: 700 mm
Y: 700 mm
Z: 600 mm



CRYSTA-Apex V162012



CRYSTA-Apex V203016



CRYSTA-Apex V9106

Measuring range

X: 900 mm
Y: 1000 mm
Z: 600 mm



CRYSTA-Apex V122010

Measuring range

X: 1200 mm
Y: 2000 mm
Z: 1000 mm

Note: All models incorporate a main unit Startup system (relocation detection system), which disables operation when an unexpected vibration is applied or the machine is relocated. Be sure to contact your nearest Mitutoyo Sales Office prior to relocating this machine after initial installation.

HIGH PRECISION




Absolute quality


Provides a performance specification unmatched by any previous CMM of this class through features that include an advanced real-time thermal compensation system which makes measurement accuracy practically independent of temperature changes in the environment. This is in stark contrast to earlier generation CMMs where accuracy could not be guaranteed unless the machine was installed in the controlled environment of a measuring room held as closely as possible at the standard temperature of 20 °C.

Real-time temperature compensation

The Mitutoyo thermal compensation system technology enables the CRYSTA-Apex V Series to maintain specified accuracy over the wide temperature range of 16-26 °C. The system operates by continuously tracking the temperature of the workpiece and every scale on the CMM and using this data to calculate and apply corrections to the measurement output. Thus the CMM appears to be performing as if it is always operating at a constant temperature of precisely 20 °C.




Graph showing the effectiveness of temperature compensation



High accuracy in the 1.7 µm class

The CRYSTA-Apex V Series guarantees a maximum permissible length measurement error ($E_{0,MPE}$) of $1.7 + 3L/1000 \mu\text{m}$, a specification that compares very favorably with a standard CMM offering an $E_{0,MPE}$ of $2.5 + 4L/1000 \mu\text{m}$, which would generally be considered high accuracy. To illustrate the practical advantage of the higher specification of the CRYSTA-Apex V Series, consider the case where the tolerance is $\pm 0.02 \text{ mm}$: the measurement uncertainty of the standard machine exceeds one-fifth of this tolerance* for any length over 375 mm. In contrast, the V Series uncertainty remains within one-fifth of the tolerance for measured lengths up to 766 mm. Hence the V Series actually offers guaranteed accuracy over more than double the measuring range of the less accurate standard machine.



* Assuming an acceptable working ratio between component tolerance and accuracy of measurement is 5:1 minimum.

Repeatability

Excellent measurement repeatability is essential for high accuracy and this is especially true when using scanning probes to measure complex 3D surfaces, an application where dynamic errors can occur if precautions are not taken. In this scenario, the data from the scanning probe is stabilized by holding the probe stationary for a short time whenever the stylus tip contacts the workpiece, thereby ensuring that inertial causes of dynamic error are eliminated, making it possible to deliver the best possible level of repeatability obtainable from the CRYSTA-Apex V Series machines.



HIGH SPEED

Dramatically reduces measurement time with high-speed measurements

The V Series enables users to freely set measurement paths along three-dimensional surfaces, enabling complex workpieces to be measured most efficiently. High-speed measurement is unaffected by processing accuracy through real-time correction of path errors caused by differences between workpiece and design values. The V Series, with its high drive speed and acceleration combined with a maximum measuring speed of 8 mm/s, dramatically reduces total measuring time.



Speed and acceleration to reduce measurement time

The CRYSTA-Apex V Series offers a maximum drive speed of 519 mm/s and a maximum acceleration of 2,309 mm/s². Compared with conventional CNC CMMs (typically around 430 mm/s and 1,650 mm/s²), this amounts to about 100 mm more traverse distance one second after starting movement. This faster movement capability, combined with a maximum measuring speed (the speed with which the stylus traces over the workpiece) of 8 mm/s, much faster than conventional CNC CMMs (typically around 5 mm/s), cuts total measuring time significantly. The more measurement locations, the greater this margin grows, which in turn results in significant cost savings.




High-speed optimum path scanning

The V Series is equipped with a measurement feature that allows users to specify scanning measurement paths (design values). This feature allows for high speed, high-accuracy scanning by correcting dynamic errors that would otherwise be produced by acceleration and deceleration stresses. Measurement paths can be freely specified for three-dimensional forms as well, which enables intricate workpieces to be measured by tracking precisely along their curved surfaces and contours.



Active scanning feature

Enables high-speed measurement by accommodating discrepancies between design values and the actual workpiece. The 3D optimal path scanning advantages are retained while allowing for manufacturing or alignment deviations. The complexity of some workpieces. (e.g. turbine blades, fan blades and impellers) makes measurement difficult, as their manufacturing variation fluctuates more than most machined parts. The V Series can tolerate these differences and still perform accurate measurement.



DIVERSITY

Efficient, high-accuracy measurement of practically any part shape


The CRYSTA-Apex V Series is suitable for a wide range of applications using touch-trigger, scanning and non-contact probes in fully automatic part-program measurement cycles.

SurfaceMeasure 201FS Mitutoyo
FLYING SPOT LASER PROBE

Probes for Coordinate Measuring Machines


5-axis Control touch-trigger probe system PH20

The PH20 head can position a touch-trigger probe at any angle, allowing unique "head touch" probing. This system has the advantage of measuring tilted surfaces and small, deep holes. There is no fear of interference from the stylus shank during measurement of a deep hole. 5-axis operation reduces the time required for probe rotational movements and supports "head touch" operation for quick point measurement.




Compact high-accuracy scanning probe SP25M

The SP25M is a compact, high-accuracy scanning probe with a 25-mm outside diameter. It is a multi-function CNC CMM probe that can collect data not only from scanning measurements, where the probe moves while in contact with the workpiece to collect a point-cloud of coordinate values, but from high-accuracy single-point measurements as well.



Non-contact laser probe SurfaceMeasure

SurfaceMeasure is a non-contact probe that collects coordinate values of the surface of a workpiece by using laser light. It can quickly obtain a point-cloud of 3D surface data.



Measuring color sample boards

Measuring glossy workpieces




Efficient, high-accuracy measurement in a variety of applications

The CRYSTA-Apex V Series is suitable for a wide range of applications using touch-trigger, scanning and non-contact probes in fully automatic part-program measurement cycles.

Electric-cell separator molds

Electric vehicle



Surface and cross-section measurements on precision molds for the separators used in electric cells can be made using a low measuring force, high-accuracy scanning probe. Three-dimensional error and cross-sectional form analyses may be performed using the measurement data obtained.

Pump impellers


Automobile



Complex shapes such as pump impellers can be measured using a robust non-contact laser probe that produces huge amounts of data in the form of a point cloud to provide highly detailed measurement data for excellent characterisation of the part.

Electric motor cores

Electric vehicle



Surface and cross-section measurements on precision moulds for the separators used in electric cells can be made using a low measuring force, high-accuracy scanning probe. Three-dimensional error and cross-sectional form analyses may be performed using the measurement data obtained.

Turbine and fan blades

Aircraft



The cross-section of aircraft engine aerofoil components can be measured using a compact, high-accuracy scanning probe. Even workpieces susceptible to large errors, such as castings, can be measured quickly and reliably.

Artificial joints

Medical care



Freeform surface measurement of artificial joints can be made using a compact, high-accuracy scanning probe. Three-dimensional error analysis can be performed using the measurement data obtained.

Transmission cases

Power trains




Non-contact laser probes require dramatically less measurement time compared to contact (scanning) probes. Scanning from three directions enables simultaneous measurement of the top and side faces, which means less repositioning and efficient measurement of even the most intricate parts.

SOFTWARE

Application software that offers functionality and ease of use

Mitutoyo offers an extensive choice of application software for automatically generating part programs to perform measurement and evaluation of simple or complex components, including gears and aerofoils. Practically any measurement challenges that our customers may encounter can be tackled by V Series machines.






MCOSMOS

Data processing


MCOSMOS is the Mitutoyo suite of PC-based CMM software applications that consists of optional modules to support fully automated measurement of all kinds.



MiCAT Planner

Automatic part-program generating


This software package dramatically reduces part-programming creation time by automatically generating the part program. Tolerance information from a 3D CAD model is read to determine which features of the part should be measured to verify conformance to specification. Compared to conventional methods (teaching), this method creates more-efficient measurement programs as well as saving time.



MSURF

Scanning and evaluation by laser probe

The MSURF software package comprises MSURF-S for scanning measurement of a part and MSURF-I for comparing the resulting measurement data against the master model data.



SMART FACTORY


From status management to preventive maintenance. Kickstart your smart factory through visualization.

Mitutoyo has developed new features that use a network to centrally manage manufacturing process information. The MeasurLink® software package helps prevent defective parts by collecting and analyzing measurement data in real time. The status monitor (SMS: Smart Measuring System), which indicates the operational status of the measuring machine; and the condition monitor, which indicates the physical condition of the machine itself, help maintain measurement accuracy, increase productivity, and improve maintenance management.



Status Monitor


Can remotely monitor measuring machines





Condition Monitor

Conduct preventive maintenance through CMM status monitoring




Output information

- Slideway distance travelled
- Temperature log
- Number of probe inputs
- Other selectable information

Preventive maintenance through status monitoring

MeasurLink®

Reduces defective products by visualizing quality



Note: MeasurLink® is a registered trademark of Mitutoyo Corporation in Japan and Mitutoyo America Corporation in the United States.

USABILITY

Effectively reduces operation and measurement time through enhanced convenience and usability

The V Series is equipped with the Quick Launcher to improve operability and a joystick box that allows users to remotely control their measuring machine as though it were right in front of them. These enhancements in usability enable the workflow to be streamlined by reducing measurement time.

Part program execution

The Quick Launcher enables simple and intuitive operation for easy part program execution. The touch-panel monitor further improves operability, making operations practically effortless for anyone. Part programs can also be executed via barcodes and QR codes.




Joystick box

The joystick box allows users to easily operate their CRYSTA-Apex V Series CMM from a remote location. It comes with control buttons marked with user-friendly icons and an override knob for changing speed.



MiCAT Planner

This software package dramatically reduces part-programming creation time by automatically generating the part program. Tolerance information from a 3D CAD model is read to determine which features of the part should be measured to verify conformance to specification. Compared to conventional methods (teaching), this method creates more-efficient measurement programs as well as saving time.



OPTIONS

To support fully automated measurement and efficient setups

Options that support fully automated measurement to capitalize on the advantages of CNC CMMs, and that promote efficient setups to reduce cycle time.

Automation example

The V Series' ability to deliver high-accuracy measurements across a wide temperature range eliminates the need for a dedicated measuring room. This allows for the automation of in-line and line-side measurements within the manufacturing process to significantly reduce measurement time and streamline the workflow.





Clamping system Eco-Fix Kit

Mitutoyo clamping tools comprise of a clamping system where elements can be put together like toy construction blocks to easily fix workpieces in place on the measuring table.



Rotary table

This is a precision orientation device for CNC CMMs to aid efficient and high-accuracy measurement of rotational-form components such as gears, impellers, screw rotors and cams. Can be synchronized with a scanning probe to enable a wide range of contour measurements to broaden the application range of a CMM.





Whatever your challenges are, Mitutoyo supports you from start to finish.

Mitutoyo is not only a manufacturer of top quality measuring products but one that also offers qualified support for the lifetime of the equipment, backed by comprehensive services that ensure your staff can make the very best use of the investment.

Apart from the basics of calibration and repair, Mitutoyo offers product and metrology training, as well as IT support for the sophisticated software used in modern measuring technology. We can also design, build, test and deliver measuring solutions and even, if deemed cost-effective, take your critical measurement challenges in-house on a sub-contract basis.



Find additional product literature and our product catalog

www.mitutoyo.com

Note: All information regarding our products, and in particular the illustrations, drawings, dimensional and performance data contained in this printed matter as well as other technical data are to be regarded as approximate average values. We therefore reserve the right to make changes to the corresponding designs. The stated standards, similar technical regulations, descriptions and illustrations of the products were valid at the time of printing. In addition, the latest applicable version of our General Trading Conditions will apply. Only quotations submitted by ourselves may be regarded as definitive. Specifications are subject to change without notice.

Mitutoyo products are subject to US Export Administration Regulations (EAR). Re-export or relocation of our products may require prior approval by an appropriate governing authority.

Trademarks and Registrations

Designations used by companies to distinguish their products are often claimed as trademarks. In all instances where Mitutoyo America Corporation is aware of a claim, the product names appear in initial capital or all capital letters. The appropriate companies should be contacted for more complete trademark and registration information.



Mitutoyo America Corporation

www.mitutoyo.com
 One Number to Serve You Better
 1-888-MITUTOYO (1-888-648-8869)

M³ Solution Centers:

- Aurora, Illinois (Headquarters)
- Boston, Massachusetts
- Charlotte, North Carolina
- Cincinnati, Ohio
- Detroit, Michigan
- Los Angeles, California
- Seattle, Washington
- Houston, Texas